



Schindler PORT 3 Outdoor

The all-weather access control reader



Schindler PORT 3 Outdoor Specifications

A durable access control reader for exterior entrances and low-traffic interior doors. PORT 3 Outdoor can be integrated into any PORT system.

Product dimensions and views

Surface mounting

Flush mounting

Color options

Black

White

Space Grey

All dimensions are in mm (inch)

Properties and dimensions

Physical Dimensions (W×H×D)	Surface mount: 86×86×67 mm (3.39×3.39×2.64 inch) Flush mount: 86×86×35 mm (3.39×3.39×1.38 inch)	Mounting Height	The centerline is 1100 mm (43.31 inch) above the finished floor level
Power Supply	24 V (9–30 V)	Card Reader	Supports all common RFID tags (all tags must be prequalified by our test service center prior to installation)
Power Consumption	max. 3 W	Standby Mode	No
Range of Application	Temperature: -25 to 80 °C (-13 to 176 °F) Humidity: 5 to 95 % Outdoor use (ingress protection IP55)	Additional Features	Connects to PORT Door Controller over RS485 (USB optional)

Schindler Management Ltd.
Zugerstrasse 13
6030 Ebikon
Switzerland
+41 41 445 30 60

www.schindler.com

We Elevate

This publication is for general informational purposes only and we reserve the right at any time to alter the product design and specifications. No statement contained in this publication shall be construed as a warranty or condition, expressed or implied, as to any product, its fitness for any particular purpose, merchantability, quality or shall be interpreted as a term or condition of any agreement regarding the products or services contained in this publication. Minor differences between printed and actual colors may exist.

Copyright © 2023 Schindler Aufzüge AG